EM Series® Electronic Manual Dispense Meters



Designed for the Harshest Environments



EM Series® Electronic Manual Dispense Meters

EM Series handheld and in-line meters are designed to last – from small service centers and lubrication trucks to heavy-duty repair facilities. Choose from 8 or 20 gpm (30.3 to 75.7 lpm) hand-held models or our 20 gpm (75.7 lpm) in-line meter. Graco's EM Series meters are backed by our robust warranty and feature upgraded electronics and easy-to-read LCD with simple operator controls that measures in quarts, gallons, pints and liters.

Proven in Harsh Conditions

Sealed electronics (IP69K) are protected against direct pressure washing and dust.

Long Battery Life

Features upgraded electronics and easily replaceable AAA batteries.

Twist-Close Nozzle Prevents Leaking

Multiple extensions available including rigid, flexible and gear lube.

High-Flow Rates

Capable of up to 20 gpm.

Legacy Valve

1/2 and 3/4 inch inlets, compatible with oil, ATF, anti-freeze and gear lube.

Prevent Accidental Dispenses

Easy-to-hold locking handle.

Ordering Information

	Extension	Inlet in (mm)	Part Number		
			NPT	BSPT	BSPP
	Flexible	1/2 (13)	25C904	25C912	25C908
EM8	Rigid		25C903	25C911	25C907
	Gear		25C905	25C913	25C909
	Flexible	1/2 (13)	25C915	25C921	25C924
EM20		3/4 (19)	25C918	250927	25C930
	Rigid	1/2 (13)	25C916	25C922	25C925
		3/4 (19)	250919	250928	250931

EM Series® IM In-Line Electronic Meter

Easy-to-Read LCD

Simple operator control. Measures in quarts, gallons, pints and liters.

Easy Battery Replacement

Long-lasting, replaceable AAA batteries.



Sealed Electronics

IP69K-rated meter. Electronics are safe from pressure washing and dusty environments.

Easily Track Fluid Usage

Track individual dispenses or display total dispense history.

Ordering Information

Part Number	Part Number Description 25C841 IM20 high-flow, high-pressure in-line meter	
25C841		

chnical Specifications	EM8	EM20	IM20		
Flow Range	0.25 to 8 gpm (0.95 to 30.3 lpm)	0.25 to 20 gpm (0.95 to 75.7 lpm)	0.25 to 20 gpm (0.95 to 75.7 lpm)		
Maximum Operating Pressure	1,500 psi (102 bar)				
Unit of Measure	Quarts, gallons, pints, liters				
Accuracy/Repeatability	±0.5%				
Inlet	1/2 in NPT 1/2 in BSPP 1/2 in BSPT	1/2 in NPT or 3/4 in NPT 1/2 in BSPP and 3/4 in BSPP 1/2 in BSPT and 3/4 in BSPT	3/4 in NPT		
Outlet	3/4 in straight thread O-ring boss	7/8 in straight thread O-ring boss	3/4 in NPT		
Maximum Totalizer	19,999 units				
Maximum Recorded Dispense	19,999 units				
Operating Temperature Range	-22°F to 180°F (-30°C to 82°C)				
Storage Temperature Range -40°F to 185°F (-40°F to 185°F (-40°C to 85°C)			
Outdoor Use	Yes – IP69k as per DIN 40050-9				
Battery	2 (AAA) alkaline or 2 (AAA) lithium				
Wetted Parts	Aluminum, stainless steel, carbon steel, acetal, nitrile rubber, Geolast™				
Meter Pressure Loss*	30 psi @ 6 gpm (2.07 bar @ 22.7 lpm)	85 psi @ 12 gpm (5.86 bar @ 45.4 lpm)	35 psi @ 12 gpm (2.41 bar @ 45.4 lpm)		
Dimensions	13 in L x 3.5 in W x 5.25 in H (33 cm L x 9 cm W x 13.3 cm H)		4.2 in L x 3.4 in W x 3.2 in H (10.7 cm L x 8.6 cm W x 8.1 cm H)		
Weight	3 lbs (1.36 kg)	3.1 lbs (1.39 kg)	1 lb. 4 oz. (0.57 kg)		
Warranty Five years overall, three years electronics and or		overall, three years electronics and one year	wear parts		
Instruction Manual	3A5588				

^{*}Tested in 10W oil at 70°F (21°C). Flow rate varies with fluid pressure, temperature, viscosity, inlet fitting size and nozzle type. Geolast is a registered trademark of Advanced Elastomer Systems.

Typical Applications

- Automotive dealerships
- · Service and fast lube centers
- Lube trucks
- Mining
- Heavy-duty dealerships
- · Fleet service facilities
- In-plant

Typical Fluids Handled

- Petroleum- and synthetic-based oils (motor, gear and ATF)
- Anti-freeze

>>> Ordering Information

Accessories

Part Number	Description	
25D934	Electronic control replacement	
129876	Black impact guard for EM8, EM20 and IM20	
25D936	Battery kit: includes AAA batteries, Torx screws and bezel seal	

Hose Identification Sets

Vinyl hose wrap for easy identification of meter fluid.

	Part Number	Description
OGRACO	17S659	Red
GGRACO	17S660	Blue
O GRACO	17S661	Green
Ograco	17S662	Yellow
OGRACO	17S663	White

AMERICAS

MINNESOTA

Worldwide Headquarters Graco Inc. 88 11th Avenue N.E. Minneapolis, MN 55413

MAILING ADDRESS

P.O. Box 1441 Minneapolis, MN 55440-1441 Tel: 800-275-5574 Fax: 612-623-6777

EUROPE

BELGIUM

Graco BVBA Industrieterrein-Oude Bunders Slakweidestraat 31 B-3630 Maasmechelen, Belgium Tel: 32 89 770 700 Fax: 32 89 770 777

ASIA PACIFIC

AUSTRALIA

Graco Australia Pty Ltd. Suite 17, 2 Enterprise Drive Bundoora, Victoria 3083 Australia Tel: 61 3 9468 8500 Fax: 61 3 9468 8599

CHINA

Graco Fluid Equipment (Shanghai) Co., Ltd.
Building 7, No.1-2
Wenshui Road 299,
Jing'an District
Shanghai 200436
P.R.China
Tel: 86 21 649 50088 Fax: 86 21 649 50077

INDIA

Graco Hong Kong Ltd. India Liaison Office Room 443, Level 4 Augusta Point, Golf Course Road Gurgaon, Haryana, India 122001 Tel: 91 124 435 4208 Fax: 91 124 435 4001

JAPAN

Graco K.K. 1-27-12 Hayabuchi Tsuzuki-ku Yokohama City, Japan 2240025 Tel: 81 45 593 7300 Fax: 81 45 593 7301

KOREA

Graco Korea Inc.
Shinhan Bank Building
4th Floor #1599
Gwanyang-Dong, Dongan-Ku,
Anyang-si, Korea 431-060
Tel: 82 31 476 9400 Fax: 82 31 476 9801

©2019 Graco Inc. 352673 Rev. D 6/19 All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice. For more information on Graco's intellectual property, see www.graco.com/patent or www.graco.com/trademarks.



Graco's got you covered

Facilities Worldwide for Global Support



Quality First

At Graco we pride ourselves on providing best-in-class products. Engineered solutions are manufactured in our own facilities, with the highest standards in the industry. We provide you with world-class customer support and expertise to help solve your lubrication challenges.



Global Reach

Graco has facilities and distribution partners across the globe to provide you with the products and service *you* need, where *you* live. Plus, Graco has dedicated field experts in all areas of the world to support the products we sell.



Product Capabilities

Graco has a broad range of products to provide solutions that meet your needs. Our products are engineered and tested to perform in the harshest environments so you can be certain your equipment is protected and working at peak performance.

Contact us today!

Call **800-533-9655** to speak with a Graco representative, or visit **www.graco.com** for more information.

